

# EUROPEAN PATENT OFFICE

## Patent Abstracts of Japan

PUBLICATION NUMBER : 63277165  
PUBLICATION DATE : 15-11-88



APPLICATION DATE : 06-05-87  
APPLICATION NUMBER : 62108911

APPLICANT : NIPPON STEEL CORP;

INVENTOR : ABE KIYOSHI;

INT.CL. : B65H 20/10 C21D 9/56 C23C 2/00  
C25D 7/06

TITLE : FLUID SUPPORTING PAD USED IN  
LIQUID



ABSTRACT : PURPOSE: To improve the workability of a product after plating as well as to improve the surface quality of the product by using a noncylindrical fluid supporting pad with a convexly curved surface of less than a semicircle, for only the surface to be opposed to a strip metal in plate of a cylindrical fluid pad.

CONSTITUTION: As compared with a cylindrical pad, it is good enough to be only a part equivalent to length as long as  $h_1$  of less than  $1/2$  in a diameter  $2r$  so that the length of a strip metal 1 being dipped in a plating bath 12 is reducible. In consequence, the dipping time is reducible as well. Since an arc surface 11 is provided with a liquid exhaust nozzle 10, the strip metal 1 is conveyed in noncontact with the arc surface 11 of a pad 2 in a state of sticking metal plating on the surface, and it is drawn out of the plating bath 12 in a short time. And, if this pad 2 is used, longitudinal length can be shortened so that a liquid quality in a liquid tank can be reduced as much as a portion equivalent to the part reduced in length, therefore energy required for heating and hot insulation is reducible as well.

COPYRIGHT: (C)1988,JPO&Japio